

PERA
Ray
RLS

MONITOR WELL PRE-SPUD PROPOSAL

1) WELL NAME/NUMBER: 700-D

2) PROPOSED LOCATION: (a) General (on or off-site) On-site

(attach map Site Area 700-Area Landfill

(b) Sect 26 Twnshp 20S Rng 3E SE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ NE

$\frac{1}{4}$

3) WELL PARAMETERS:

(a) Est. total depth 400 (ft) (b) Est. ground elevation 4900 ft

(c) Anticipated stratigraphy:

Alluvium (Santa Fe Group) from 0 ' to 200 ' (depth)

Limestone from 200 ' to TD ' (depth)

(d) Anticipated water bearing horizon(s):

Limestone at 230 ' (depth)

(Look for a productive fracture)

(e) Anticipated static water level 220 ' (depth)

4) WELL PURPOSE/JUSTIFICATION (attach maps and table if needed):

Investigate groundwater quality downgradient from the 700 Area Landfill.

5) PROPOSED DRILLING PARAMETERS:

(a) Drilling method(s): (air/foam/mud rotary/auger/etc.)

Mud Rotary from 0 ' to 100 (max) ' (depth)

Air-Foam Rotary from 100 ' to TD ' (depth)

Air-foam method: "Quik-Foam" surfactant/water mixture used in conjunction with filtered compress air.

Mud-rotary method: Bentonite mud/water mixture.

WELL NAME/NUMBER: 700-D

- (b) Lithology sampling - collect sample every:

5' intervals Method Grab from 0 ' to TD ' (depth)
Core type 6" Dennison from _____ ' to None ' (depth)
2" Christiansen from _____ ' to None ' (depth)

- (c) Anticipated drilling additive(s): None

7) **PROPOSED WELL COMPLETION DESIGN/MATERIALS**

(a)	Casing:	<u>Material</u>	<u>Diameter</u>	<u>From</u>	<u>To</u>	<u>Comments</u>
	Temporary	_____	_____	_____	_____	_____
	Surface	_____	<u>10"</u>	<u>0</u>	<u>100' max</u>	_____
	Screen (10')	<u>stainless ++</u>	<u>4"</u>	<u>determine from geophysical logs</u>		
	Completion Pipe	<u>stainless +</u>	<u>4"</u>	<u>0</u>	<u>TD</u>	<u>*</u>

Standard material: Blank riser, silt trap, locking cap

N/A Data not available at this time

* for deep completions (450 feet or more)

** for shallow completions

+ Type 304, Schedule 5 stainless steel

Type 304, Schedule 10 stainless steel

++ Regular strength screen, extra strength screen used below 450 feet

- (b) Filter pack: Standard 8/20 and 16/40 sand and bentonite plug(s), grout to surface.

8) **PROPOSED WELL DEVELOPMENT**


- (a) Surge and bail with surge block and bailer.

- (b) Pump with submersible pump until parameters stabilize.

9) **WELL AUTHORIZATION**

- (a) Proposed by Geoscience Consultants, Ltd.

- (b) Authorized Robert Mitchell NASA
(name) (representing)


(signature)

